#### **Lubricating the Tracks**

We recommend using a non-petroleum based silicone to lubricate the track assembly.



With the vinyl in its up position, spray the section of track that the vinyl is retained in. Roll the vinyl down, then spray the edge where it contacts the track. Let dry and any "sticking" should disappear. Depending on your location, this process should be performed every 3-6 months.

Additional cans of our SKEET'R BEAT'R Spray Silicone are available from your Screen America Authorized Dealer.





Highfield Door Sales
1350 EAST STROOP ROAD
KETTERING, OH 45429
937-293-2531
www.highfielddoorsales.com

# Care and Maintenance of


## **Vinyl Systems**



7269 W Homosassa Trail Homosassa, FL 34448 352.628.5512 800.764.1110

# Congratulations on the Purchase of Your Vinyl System!

After installation, you will receive a blue warranty registration card to be filled out by the dealer or yourself. It is important for this card to be returned to Screen America Corporation so that your unit's information can be recorded and registered in our database.



Our standard warranty includes five years on the motor, one year on the balance of the electronics, and a limited life time warranty detailed on the warranty card.

### Cleaning the Vinyl, Housing & Aluminum Track

To extend the life of your vinyl system, we recommend the following:

- Monthly (with normal use) apply a solution of water mixed with a non-abrasive liquid detergent (Dawn dish soap) using a soft cloth, to both front and back of the vinyl.
- 2. Rinse completely and dry with a soft cloth or chamois.

#### DO NOT SPRAY INSIDE THE MOTOR OR HOUSING UNIT

3. Apply 303 Aerospace Protectant according to directions.

Contact your Screen America Authorized Dealer to see if they offer a maintenance program that suits your needs.

#### **CAUTION**

The vinyl system is **not** designed to protect interior areas in adverse windy conditions. If this situation arises, your vinyl system should be rolled up to protect it from damage.

#### Monthly (with normal use)



Follow the directions on the 303 Aerospace Protectant by applying a thin layer to both front and back of the vinyl. Wipe completely dry with a soft cloth. (If streaking occurs, too much product has been applied and can be removed by using a damp towel and finishing with a dry, soft cloth). To increase the longevity, repellency, and bonding of the product, periodic buffing with a soft, dry cloth is recommended.

Additional cans of 303 Aerospace Protectant are available from your Screen America Authorized Dealer.